

ALLURE LIGHT 8119



With the Allure light, Braslux offers an innovative solution that combines versatility, contemporary design, and the well-known Braslux quality standard.

It features a rectangular design with softly rounded edges, hidden LEDs, and a smoked lens, allowing for a harmonious and discreet integration into vehicle designs, elevating them to a new level of sophistication.

- Floating lens
- ECE Approved
- Homogeneous lighting

SUGGESTED APPLICATIONS



Illustrative image.

TECHNICAL DATA:

Part number	Rated voltage	Connection	Power consumption Tail light	Power consumption Stop light	Power consumption Directional indicator	Power consumption Reverse light	Power consumption Rear fog light	Lens material	Housing material	Mounting	Maximum torque	Weight
8119.83.306	12/24V	AMP 4V	0,5W	3,3W	2,2W	-	-	PMMA	ABS	Rear fixing	3,0 N.m	0,2 Kg
8119.82.306	12/24V	AMP 3V	-	-	-	2,0W	6,7W	PMMA	ABS	Rear fixing	3,0 N.m	0,2 Kg

ECE HOMOLOGATED	IP IP6K7	UV 1500h (housing) / 1500h (lens)
970 CONTRAN HOMOLOGATED	TEMP -40°C to 50°C	EMC R10 CISPR25 CLASSE III
		Patented Braslux

For more information, visit the website www.braslux.com.br

TECHNICAL DRAWING:

